

# HSF RoHS




REV	ECN NO	DESCRIPTION	DATE	NAME
A		NEW		

## Specifications

1. Current Rating: 3Amps
2. Contact Resistance: 20mΩ
3. Insulator Resistance: 1000 Megohms min.
4. Dielectric withstanding Voltage: AC/DC 1000V
5. Operating Temperature: -40℃ to +105℃
6. Contact Material: Copper alloy
7. Insulator Material: As follows
8. Plated: As follows

## Ordering Information


L308 XX -XX 1 X X XX X



Insulation Height*Wide (H*W) Option:	NO. of Pins Per Row: 1-40P	Insulation Material Option:	Contact Plating Option:	Serial NO.	Packing
50=5.0*5.0		1=PBT	0=0.8" Gold	01-69 (No pillars)	A=PE Bag
57=5.7*5.0		2=PPS	1=Au1" Gold	70-89 (pillars)	B=Tube
71=7.1*5.0		3=NY6T	2=Au1.5" Gold	90-99 (outside pillars)	C=Tray
80=8.0*5.0		4=LCP	3=Au2" Gold		D=Reel
85=8.5*5.0		5=NY66	4=Au3" Gold		
		6=Customized	5=Au5" Gold		
		7=NY46	6=Customized		
		8=NY9T	7=Gold/Tin		
			8=Tin		

### Dimension antitheses list

ITEM	PC	H	W
Standard	3.0	5.0/5.7/7.1/8.0/8.5	5.0
Alternate			



PCB LAYOUT

STANDARD TOLERANCE (EXCEPT SPECIFIED)			
LINER		ANGLES	
.0	±0.30	0.°	±3°
.00	±0.20	.0°	±2°
.000	±0.10	.00°	±1°

## LDCONN 东莞连大精密制品有限公司

大 DongGuan LianDa Precision Products Co., LTD

TITLE	PH2.54mm 2XNP 90° Dual row Female Header Y Type	DRAWN BY	Lujunhui	18.04.03
PART NO	L308XX-XX1XXXXX	CHECKED BY		
DRAWING NO		APPROVED BY		
SCALE	1:1	UNIT	mm	PAGE 1/1
				SIZE A4